

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number  
**WO 2005/076253 A1**

(51) International Patent Classification<sup>7</sup>: **G09G 3/32**

(21) International Application Number:  
PCT/GB2005/000419

(22) International Filing Date: 7 February 2005 (07.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0402640.7 6 February 2004 (06.02.2004) GB

(71) Applicant (for all designated States except US): **PELIKON LIMITED** [GB/GB]; Unit 6, Bar Hill Business Park, Saxon Way, Cambridge CB3 8SL (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FRYER, Christopher, James, Newton** [GB/GB]; 149 High Street, Cottenham, Cambridgeshire CB4 8SD (GB). **BLAKESLEY, Richard, Guy** [GB/GB]; 3 Hurrell Road, Cambridge CB4 3RQ (GB).

(74) Agent: **FRANK B. DEHN & CO.**; 179 Queen Victoria Street, London EC4V 3EL (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AMBIENT LIGHT SENSOR



(57) Abstract: A light-emitting display having display areas (14), which may be lit or unlit, comprising a sensor (13) for ambient light, in which the display is arranged to use an output of the sensor (13) to modify the brightness of the display areas (14) when lit in dependence upon the ambient light conditions, the sensor being hidden behind an unlightable section of the display. The display is particularly advantageously an electroluminescent display.

WO 2005/076253 A1

### Ambient Light Sensor

5 This invention is concerned with improved displays, and relates in particular to displays, such as electroluminescent displays, that employ an ambient light sensor used to allow their brightness and contrast to be adjusted in dependence upon the ambient light conditions.

10 Certain materials are electroluminescent - that is, they emit light, and so glow, when an electric field is generated across them. The first known electroluminescent materials were inorganic particulate substances such as zinc sulphide, while  
15 more recently-found electroluminescent materials include a number of small-molecule organic emitters known as organic LEDs (OLEDs) and some plastics - synthetic organic polymeric substances - known as light-emitting polymers (LEPs). Inorganic  
20 particulates, in a doped and encapsulated form, are still in use, particularly when mixed into a binder and applied to a substrate surface as a relatively thick layer; LEPs can be used both as particulate materials in a binder matrix or, with some advantages,  
25 on their own as a relatively thin continuous film.

This electroluminescent effect has been used in the construction of displays. In some types of these a large area of an electroluminescent material - generally referred to in this context as a phosphor -  
30 is provided to form a backlight which can be seen through a mask that defines whatever characters the display is to show. In other types there are instead individual small areas of EL material. These displays have many applications; examples are a simple digital  
35 time and date display (to be used in a watch or clock), a mobile phone display, the control panel of a household device (such as a dishwasher or washing

machine), and a hand-holdable remote controller (for a television, video or DVD player, a digibox, or a stereo or music centre).

5 The visibility of electroluminescent displays is dependent upon the contrast between those areas of the display that are turned on ("lit") and those that are not; this contrast is the result of the lit areas being both brighter than the surrounding areas ("luminance contrast") and often also a different  
10 colour ("chrominance contrast"). The brightness and colour of the lit areas is a function of the particular electroluminescent material being utilised and of the degree to which it is energised. The brightness and colour of the unlit areas is dependent  
15 on the light reflected off their surface, which in turn is a function of the ambient light level and the materials used to make up the display (which might include filters and anti-reflective coatings).

Many displays - television remote controllers,  
20 for example - are used in a wide range of ambient light levels. As the ambient light level increases, so the amount of light reflected from the off-state areas increases - and hence the luminance contrast decreases for a fixed brightness emitted by the  
25 on-state. While setting the display brightness such that it is visible in the highest expected ambient light level will mean that it can be seen in all expected ambient light levels, this has the disadvantages of increased power consumption and  
30 shorter display lifetime. Also, in some dark usage conditions the display can appear excessively bright and distracting. The invention proposes dealing with this problem by building in to the display a sensor for the ambient light, and then using the sensor's  
35 output to modify the lit areas' brightness appropriately (so that those areas are brighter in

strong ambient light and of reduced brightness in weak ambient light).

In one aspect, therefore, this invention provides a light-emitting display wherein there is the  
5 necessity for a clear contrast between the display's lit and unlit areas, which display incorporates a sensor for the ambient light, and the sensor's output is utilised to modify the lit areas' brightness appropriately in dependence upon the ambient light  
10 conditions.

The light-emitting display can be of any sort - it could, for instance, be a light-emitting diode (LED) display, or it could be a backlit liquid crystal display (an LCD) or even a thin film  
15 transistor (TFT) display as used in computer screens - but the invention is of particular value when applied to displays using electroluminescent materials to provide the light output.

The light sensor may take any convenient form, and be of any suitable type. It may, for example, be  
20 a light-dependent resistor (such as the VT935G from PerkinElmer Optoelectronics) or a photodiode (such as the BPW21 from Centronic).

The sensor's output may be utilised to modify the  
25 lit areas' brightness in any appropriate fashion. For example, most modern displays incorporate a display controller - basically a single chip computer programmable to achieve the desired ends - which determines what the display is showing, and how bright  
30 it is, and most conveniently the sensor's output is simply fed to the controller and used thereby as one factor in determining the required display brightness. Typically the controller uses the sensor-supplied measure of the ambient light level  $A$  to adjust  
35 automatically the display brightness (as the ambient light level changes) according to a chosen function  $f(A)$  (where  $f(A)$  increases as  $A$  increases;  $f(A)$  can be

a calculable mathematical function, or it can actually be a look-up table holding a range of pre-calculated values appropriate to the expected range of ambient light levels A). In this way the perceived display contrast can be kept approximately constant across a range of ambient light levels, making the appearance of the display more consistent, and so significantly improving the perceived quality of the display. And, of course, by allowing the light output to be kept low in low ambient light levels the display's power consumption can be greatly reduced, and its lifetime significantly extended.

Though in principle the sensor can be placed almost anywhere within (or even adjacent) the display, nevertheless for best performance the sensitive area of the light sensor should be both within the bounds of the display and in the same plane as the display surface, so that directional incident light effects are correctly compensated.

Generally, displays take the form of panels having lightable areas spaced by unlightable areas. Most conveniently the sensor is mounted directly behind, and hidden by, one such unlightable - unused - area of the display panel (many sensors will give an acceptable performance even when measuring the ambient light through a number of display layers, such as filters, transparent conductors and dielectric layers).

By behind, we may mean at an opposite side of the panel from that through which light is emitted.

Where the display utilises a (programmable) display controller, to which the sensor's output is supplied, the display controller software may also allow the controller to ignore short-term drops in the measured ambient light level, thus preventing the display from going dim if, say, the User accidentally obscures the sensor whilst using the display.

The controller can include a facility for the User to adjust the display brightness to achieve a preferred contrast in a given ambient light level, by means of buttons or other User input. The controller  
5 can then automatically scale the brightness as before to maintain this apparent contrast as the ambient light changes.

According to a second aspect of the invention, there is provided a method of controlling a light-emitting display comprising a panel having display  
10 areas, which may be lit or unlit, and unlightable areas, the method comprising the steps of measuring ambient light conditions using a sensor mounted behind the panel, and controlling the brightness of the  
15 display areas when lit in dependence upon the measured ambient light conditions.

The perceived intensity of the display may be kept substantially constant across a range of ambient light levels.

20 The method may also include the steps of determining which display areas are lit and unlit and determining the brightness of the display dependent thereon.

The method may use the ambient light conditions  
25 to adjust the brightness of the display according to a chosen function which increases with the measured ambient light level, the function being a mathematical function or a look-up table holding a range of pre-calculated values appropriate to an expected range of  
30 ambient light levels.

The method may ignore short-term drops in measured light level.

The method may further comprising the step of scaling the brightness to maintain the apparent  
35 contrast as the ambient light changes, in line with the setting of a preferred contrast facility.

An embodiment of the invention is now described, though by way of illustration only, with reference to the accompanying diagrammatic Drawings in which:

Fig. 1 shows a simple clock-type product  
5 utilising an ambient light sensor in accordance with the invention;

Fig. 2 shows the same sort of product as shown in Figure 1, but "exploded" into its main components.

Fig. 3 shows a circuit diagram for a display  
10 product as in Figures 1 and 2; and

Fig. 4 shows a software flow diagram for a product as in the previous Figures.

Figure 1 is an example configuration for a simple clock-type product. It is a clock (generally 11) in  
15 which the time is indicated by a standard 7-segment digital display (12). A light sensor (13) is mounted behind the display facing forwards, hidden by one or more layers of the display construction (e.g. filters and dielectric layers) but not obscured by the display  
20 segments (14). Buttons (15) and (16) allow the User to control the apparent display brightness.

In the "exploded" view of Figure 2 the display 12 is mounted in front of a printed circuit board (PCB; 21). None of the PCB's components are  
25 shown here except the sensor 13, which is mounted on the reverse of the board 21 "looking" through an aperture (22) therein. The display 12 and PCB 21 are, in use mounted within a simple box-like container (23).

30 In Figure 3 is shown a circuit diagram using as the ambient light sensor a light dependent resistor (13).

The relevant parts of the system comprise a display controller (31) connected to a power source  
35 (32), a display (12: such as the one shown in Figure 1) and an ambient light sensor (13). In this case the sensor is a light dependent resistor (LDR),

which is connected to a fixed resistor (35) and an analogue controller input (36). The other terminal of the fixed resistor 35 is connected to an "enable" output (37) of the display controller 31.

5        When the display controller 31 wishes to measure the ambient light level, it drives the "enable" output 37 high. Current then flows through the fixed resistor 35 and the sensor LDR 13. The ambient light level affects the resistance of the LDR 13, and hence  
10       the voltage measured at the analogue input 36. The controller 31 then sets the brightness of the display 12 according to the required function  $f(A)$  of ambient light level  $A$  (in the case of an electroluminescent display, increasing the voltage  
15       and/or frequency of the drive waveforms applied to the display as  $A$  increases). The "enable" output 37 can be driven low (or alternatively high impedance) to minimise current consumption between measurements.

      The flow diagram of Figure 4 is a software flow  
20       diagram for a product that is used intermittently with automatic display switch-off (for example, a domestic television remote control) having an electroluminescent display. Though the flow diagram speaks for itself, its application can perhaps be  
25       better understood from the following description.

      When the display is turned on, the initial ambient light level ( $A_0$ ) is measured, and the display brightness set to  $f(A_0)$ . In many products the electroluminescent display is turned off when the  
30       product is not in use, to conserve power and extend the display lifetime. The display may be turned off automatically after a timeout period  $T$ , typically a few seconds.

      While the display is on, the current ambient  
35       light level ( $A_n$ ) is measured at regular intervals (typically, every 100ms). The display brightness is



set to  $f(A_n)$  if the last measurement ( $A_n$ ) is greater than the previous measurement ( $A_{n-1}$ ). This provides a simple method to prevent the display from flickering due to measurement noise and from dimming if the User  
5 accidentally obstructs the light sensor.

For displays that are on for longer periods, it may be better to compare the current ambient light value ( $A_n$ ) with the initial light level ( $A_0$ ), thus  
10 allowing the display to dim again after brief periods of bright illumination.

**CLAIMS**

1. A light-emitting display comprising a panel having display areas, which may be lit or unlit, and unlightable areas, and comprising a sensor for ambient light, in which the display is arranged to use an output of the sensor to modify the brightness of the display areas when lit in dependence upon the ambient light conditions, and in which the sensor is mounted behind and is hidden by an unlightable area of the panel.
2. A light-emitting display according to claim 1, in which the display is an electroluminescent display.
3. A light-emitting display according to claim 1 or claim 2, in which the display is arranged to keep the perceived intensity of the display substantially constant across a range of ambient light levels.
4. A light-emitting display according to any preceding claim, comprising a display controller which determines what the display is showing, and how bright it is, in which the output of the sensor is connected to the controller.
5. A light-emitting display according to claim 4, in which the controller is arranged use the output of the sensor to adjust the brightness of the display according to a chosen function which increases with the measured ambient light level, the function being a mathematical function or a look-up table holding a range of pre-calculated values appropriate to an expected range of ambient light levels.

6. A light-emitting display according to any preceding claim, in which the display is arranged to ignore short-term drops in measured light level.
- 5 7. A light-emitting display according to any preceding claim, in which the display comprises a preferred contrast facility by means of which a user can set a desired contrast level, the display being arranged to scale the brightness to maintain the  
10 apparent contrast as the ambient light changes.
8. A light-emitting display according to any preceding claim, in which the sensor is mounted within the bounds of the display panel and in the same plane.  
15
9. A method of controlling a light-emitting display comprising a panel having display areas, which may be lit or unlit, and unlightable areas, the method comprising the steps of measuring ambient light  
20 conditions using a sensor mounted behind the panel, and controlling the brightness of the display areas when lit in dependence upon the measured ambient light conditions.
- 25 10. The method of claim 9, further comprising keeping the perceived intensity of the display substantially constant across a range of ambient light levels.
11. The method of claim 9 or claim 10, further  
30 comprising the step of determining which display areas and lit and unlit and determining the brightness of the display dependent thereon.
12. The method of any of claims 9 to 11, further  
35 comprising using the ambient light conditions to adjust the brightness of the display according to a chosen function which increases with the measured

ambient light level, the function being a mathematical function or a look-up table holding a range of pre-calculated values appropriate to an expected range of ambient light levels.

5

13. The method of any of claims 9 to 12, in which short-term drops in measured light level are ignored.

10

14. The method of any of claims 9 to 13 further comprising the step of scaling the brightness to maintain the apparent contrast as the ambient light changes, in line with the setting of a preferred contrast facility.




FIG. 1






FIG. 2

2/2



# INTERNATIONAL SEARCH REPORT

Inter Application No  
PCT/GB2005/000419

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G09G3/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G09G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category.*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/214242 A1 (BERG-JOHANSEN ROAR) 20 November 2003 (2003-11-20) paragraph '0002! paragraphs '0027! - '0035! paragraph '0060! -----	1-7,9-14
X	US 6 069 597 A (HANSEN ET AL) 30 May 2000 (2000-05-30) column 1, line 32 - line 40 column 12, line 23 - line 40 column 12, line 63 - column 13, line 4 column 13, line 13 - line 57 column 14, line 39 - line 53 figures 7,9 ----- -/--	1,3-14

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

3 June 2005

Date of mailing of the international search report

24/06/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Petitpierre, 0

# INTERNATIONAL SEARCH REPORT

Inte: Application No  
PCT/GB2005/000419

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>US 6 396 217 B1 (WEINDORF PAUL FREDRICK LUTHER) 28 May 2002 (2002-05-28)</p> <p>column 2, line 27 - column 3, line 9  column 3, line 65 - column 4, line 8  column 4, line 26 - line 31  column 5, line 6 - line 24  column 5, line 59 - column 6, line 16  figures 1,2</p> <p>-----</p>	<p>1-3,  6-10,13,  14</p>



# INTERNATIONAL SEARCH REPORT

Inte Application No  
PCT/GB2005/000419

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2003214242 A1	20-11-2003	AU 2003234465 A1 WO 03098585 A1	02-12-2003 27-11-2003
US 6069597 A	30-05-2000	EP 1005689 A1 JP 2001515229 T WO 9912151 A1 US 6147664 A	07-06-2000 18-09-2001 11-03-1999 14-11-2000
US 6396217 B1	28-05-2002	DE 60102211 D1 DE 60102211 T2 EP 1220193 A2 JP 2002287720 A	08-04-2004 30-12-2004 03-07-2002 04-10-2002